

GL AOF Aluminium monté sur cadre en verre – fixe									
Modèle		2020	2028	2036	2052	2076	2828	2836	2840
Cadre extérieur (LxH)	po.	18.25 x 18.25	18.25 x 26.25	18.25 x 34.25	18.25 x 50.25	18.25 x 74.25	26.25 x 26.25	26.25 x 34.25	26.25 x 38.25
Surface vitrée (verre)	pi²	1.46	2.27	3.07	4.68	7.10	3.52	4.77	5.39

GL AOF Aluminium monté sur cadre en verre – fixe									
Modèle		2852	2860	2864	2868	2876	28100	3280	3636
Cadre extérieur (LxH)	po.	26.25 x 50.25	26.25 x 58.25	26.25 x 62.25	26.25 x 66.25	26.25 x 74.25	26.25 x 98.25	30.25 x 78.25	34.25 x 34.25
Surface vitrée (verre)	pi²	7.27	8.52	9.14	9.77	11.02	14.77	13.71	6.46

GL AOF Aluminium monté sur cadre en verre – fixe									
Modèle		3652	3660	3664	3668	3676	36100	3880	4040
Cadre extérieur (LxH)	po.	34.25 x 50.25	34.25 x 58.25	34.25 x 62.25	34.25 x 66.25	34.25 x 74.25	34.25 x 98.25	36.25 x 78.25	38.25 x 38.25
Surface vitrée (verre)	pi²	9.85	11.54	12.39	13.24	14.93	20.02	16.81	8.27

GL AOF Aluminium monté sur cadre en verre – fixe									
Modèle		4052	4064	4076	4242	4280	5252	5264	5276
Cadre extérieur (LxH)	po.	38.25 x 50.25	38.25 x 62.25	38.25 x 74.25	40.25 x 40.25	40.25 x 78.25	50.25 x 50.25	50.25 x 62.25	50.25 x 74.25
Surface vitrée (verre)	pi²	11.14	14.02	16.89	9.25	18.88	15.02	18.89	22.77

- Tous les puits de lumière peuvent être installés verticalement ou horizontalement i.e. 3652 peut devenir 5236.
- Requiert une pente minimale de 2:12.
- La boîte en bois doit avoir une épaisseur de 2po au minimum.