

GL AOF Aluminium monté sur cadre en verre - fixe									
Modèle		2020	2028	2036	2052	2076	2828	2836	2840
Cadre extérieur (LxH)	mm.	464 x 464	464 x 667	464 x 870	464 x 1276	464 x 1886	667 x 667	667 x 870	667 x 972
Surface vitrée (verre)	m ²	0.14	0.21	0.29	0.44	0.66	0.33	0.44	0.50

GL AOF Aluminium monté sur cadre en verre - fixe									
Modèle		2852	2860	2864	2868	2876	28100	3280	3636
Cadre extérieur (LxH)	mm.	667 x 1276	667 x 1480	667 x 1581	667 x 1683	667 x 1886	667 x 2496	768 x 1988	870 x 870
Surface vitrée (verre)	m ²	0.68	0.79	0.85	0.91	1.02	1.37	1.27	0.60

GL AOF Aluminium monté sur cadre en verre - fixe									
Modèle		3652	3660	3664	3668	3676	36100	3880	4040
Cadre extérieur (LxH)	mm.	870 x 1276	870 x 1480	870 x 1581	870 x 1683	870 x 1886	870 x 2496	921 x 1988	972 x 972
Surface vitrée (verre)	m ²	0.92	1.07	1.15	1.23	1.39	1.86	1.56	0.77

GL AOF Aluminium monté sur cadre en verre - fixe									
Modèle		4052	4064	4076	4242	4280	5252	5264	5276
Cadre extérieur (LxH)	mm.	972 x 1276	972 x 1581	972 x 1886	1022 x 1022	1022 x 1988	1276 x 1276	1276 x 1581	1276 x 1886
Surface vitrée (verre)	m ²	1.03	1.30	1.57	0.86	1.75	1.40	1.75	2.12

- Tous les puits de lumière peuvent être installés verticalement ou horizontalement i.e. 3652 peut devenir 5236.
- Requiert une pente minimale de 2:12.
- La boîte en bois doit avoir une épaisseur de 2po au minimum.