

AC ASF Solin aluminium intégré en dôme acrylique - fixe									
Modèle		2020	2028	2036	2052	2076	2828	2836	2840
Ouverture du toit (LxH)	mm.	368 x 368	368 x 572	368 x 775	368 x 1181	368 x 1791	572 x 572	572 x 775	572 x 876
Surface vitrée	m <sup>2</sup>	0.14	0.21	0.29	0.44	0.66	0.33	0.44	0.50

AC ASF Solin aluminium intégré en dôme acrylique - fixe									
Modèle		2852	2860	2864	2868	2876	3280	3636	3652
Ouverture du toit (LxH)	mm.	572 x 1181	572 x 1384	572 x 1486	572 x 1588	572 x 1791	673 x 1892	775 x 775	775 x 1181
Surface vitrée	m <sup>2</sup>	0.68	0.79	0.85	0.91	1.02	1.27	0.60	0.92

AC ASF Solin aluminium intégré en dôme acrylique - fixe									
Modèle		3660	3664	3668	3676	3880	4040	4052	4064
Ouverture du toit (LxH)	mm.	775 x 1384	775 x 1486	775 x 1588	775 x 1791	826 x 1892	876 x 876	876 x 1181	876 x 1486
Surface vitrée	m <sup>2</sup>	1.07	1.15	1.23	1.39	1.56	0.77	1.03	1.30

AC ASF Solin aluminium intégré en dôme acrylique - fixe						
Modèle		4076	4242	5252	5264	5276
Ouverture du toit (LxH)	mm.	876 x 1791	927 x 927	1181 x 1181	1181 x 1486	1181 x 1791
Surface vitrée	m <sup>2</sup>	1.57	0.86	1.40	1.75	2.12

- Tous les puits de lumière peuvent être installés verticalement ou horizontalement, i.e. 3652 peut devenir 5236.
- Toit de bardeaux seulement, avec un minimum de pente de 3:12 (14°).