



GL ASF

Aluminium solin intégré en verre – fixe

Tableau des tailles impériales

GL ASF Solin aluminium intégré en verre - fixe									
Modèle		2020	2028	2036	2052	2076	2828	2836	2840
Ouverture du toit (LxH)	po.	14.5 x 14.5	14.5 x 22.5	14.5 x 30.5	14.5 x 46.5	14.5 x 70.5	22.5 x 22.5	22.5 x 30.5	22.5 x 34.5
Surface vitrée (verre)	pi²	1.46	2.27	3.07	4.68	7.10	3.52	4.77	5.39

GL ASF Solin aluminium intégré en verre – fixe									
Modèle		2852	2860	2864	2868	2876	3280	3636	3652
Ouverture du toit (LxH)	po.	22.5 x 46.5	22.5 x 54.5	22.5 x 58.5	22.5 x 62.5	22.5 x 70.5	26.5 x 74.5	30.5 x 30.5	30.5 x 46.5
Surface vitrée (verre)	pi²	7.27	8.52	9.14	9.77	11.02	13.71	6.46	9.85

GL ASF Solin aluminium intégré en verre – fixe									
Modèle		3660	3664	3668	3676	3880	4040	4052	4064
Ouverture du toit (LxH)	po.	30.5 x 54.5	30.5 x 58.5	30.5 x 62.5	30.5 x 70.5	32.5 x 74.5	34.5 x 34.5	34.5 x 46.5	34.5 x 58.5
Surface vitrée (verre)	pi²	11.54	12.39	13.24	14.93	16.81	8.27	11.14	14.02

GL ASF Solin aluminium intégré en verre – fixe						
Modèle		4076	4242	5252	5264	5276
Ouverture du toit (LxH)	po.	34.5 x 70.5	36.5 x 36.5	46.5 x 46.5	46.5 x 58.5	46.5 x 70.5
Surface vitrée (verre)	pi²	16.89	9.25	15.02	18.89	22.77

- Tous les puits de lumière peuvent être installés verticalement ou horizontalement, i.e. 3652 peut devenir 5236.
- Toit de bardeaux seulement, avec un minimum de pente de 3:12 (14°).